

Condensed Catalog

# Hydra-Cell<sup>®</sup>

## Seal-less Pumps



# Hydra-Cell® Seal-less Pumps



**ISO 9001: 2015  
CERTIFIED**

<b>Contents</b>	<b>Page</b>
Overview .....	3
Principles of Operation	
Wobble Plate Models.....	4
Diaphragm Position Control .....	4
Crank-shaft Models .....	5
F/M/D/H & G Series Selection	
Flow Capacities & Pressure Ratings.....	6
F20/G20 .....	7
M03/G03 .....	7
M03/G03 Mono-Block.....	8
D04/G04 .....	8
D10/G10 .....	9
D12/G12 .....	9
D15/D17 & G15/G17.....	10
H25/G25 .....	10
D35/G35 .....	11
D66/G66 .....	11
C Series Pressure Regulating Valves.....	12
Accessories & Options .....	13
T & Q Series Design Advantages.....	14
T & Q Series Selection	
Flow Capacities & Pressure Ratings.....	15
T100 Low Pressure Models.....	16
T100 Medium Pressure Models.....	16
T100 High Pressure Models .....	16
Q155 Low Pressure Models .....	17
Q155 Medium Pressure Models.....	17
T200 Medium Pressure Models .....	18
T200 High Pressure Models.....	18
Hydra-Cell Metering Solutions	
P Series “Pulse-free” Pumps .....	19
MT8 “Pulse-free” Pump .....	20
S Series Solenoid Pumps .....	21
Additional Wanner Engineering Pumps	
Stan-Cor ANSI Centrifugal Pumps.....	22
Vector Peristaltic Pumps .....	22
Worldwide Sales & Service.....	23

“If the owner of a plant wants cost-effective pumps...he will buy pumps with the lowest Life Cycle Cost. Hydra-Cell is simple in construction, less elaborate in design and physically smaller for equivalent flow/pressure performance. These differences can substantially affect both purchase and operating costs.”

Dr. Ing Friedrich Wilhelm Hennecke  
*Chemical Engineering World*



*Due to the Wanner Engineering Continuous Improvement Program, specifications and other data in this catalog are subject to change.*

*Hydra-Cell® is a registered trademark of Wanner Engineering, Inc.*

*Kel-Cell® is a registered trademark of Wanner Engineering, Inc.*

*Control Freak™ is a trademark of Wanner Engineering, Inc.*



# Hydra-Cell® Provides Versatile, Reliable Performance



## Seal-less Design Advantages

- Positive displacement pump with hydraulically balanced, unstressed diaphragms.
- Seal-less design can handle abrasive particulates (up to 800 microns in size depending on model) and solids in suspension.
- Wide range of flow capacities and pressure ratings to meet a variety of applications in many industries.
- Heavy-duty construction for long service life in harsh conditions.
- Flexible installation with a variety of mounting configurations.
- Repeatable, accurate output with smooth, linear, virtually pulse-free flow.
- High efficiency, low power consumption.
- Minimal maintenance, no mechanical seals, cups, or packing to leak, wear, or replace.
- Can run dry without damage to the pump.

## Fluid Handling Capability

From thin liquids to highly viscous resins and slurries, Hydra-Cell pumps can handle the full spectrum of process fluids while maintaining high-efficiency operation. This includes non-lubricating fluids as well as fluids with abrasives that can damage or destroy other types of pumps.

## Primary Pumping Applications

- Adding
- Blending
- Cleaning
- Cooling
- Coating
- Dosing
- Filling
- Filtering
- Injecting
- Metering
- Mixing
- Spraying
- Transferring


## Materials of Construction Selection

- Metallic pump heads in several materials to handle higher pressures and to accommodate SAE, DIN, or ANSI flanges (where available).
- Non-metallic pump heads to process corrosive or aggressive fluids at lower pressures.
- Diaphragms and corresponding o-rings in various elastomeric materials.
- Valve assemblies in a wide range of metallic and non-metallic materials to suit specific process applications. Includes valve seats, valves, valve springs, and valve spring retainers.



Propane/ Butane    Freon    Ammonia    Polymers    Fuels/ Additives    D.I. Water    Glycols    Chlorine    Acids/ Caustics    Glues/ Adhesives    Inks/ Paints    Resins    Slurries

# Hydra-Cell® Principles of Operation



## Wobble Plate Models

- 1 Drive Shaft:** via electric motor, hydraulic motor, belt and pulley, etc.
- 2 Tapered Roller Bearings:** rigid support, immersed in lubricating oil bath.
- 3 Fixed Angle Cam/Wobble Plate:** translates rotary motion into linear to the hydraulic cells.
- 4 Hydraulic Cells (patented):** displace diaphragms via pressurized oil.
- 5 Diaphragms:** hydraulic balanced, no stress during flexing.
- 6 Inlet Valve Assembly:** simple design, allows liquid into pump chamber.
- 7 Discharge Valve Assembly:** allows liquid to flow into pressure discharge line.
- 8 C62 Pressure Regulating Valve:** controls output pressure and prevents pump overload.


## Patented Diaphragm Position Control

Diaphragm Position Control (DPC) technology protects Hydra-Cell Pumps by safeguarding the diaphragms against abnormal or adverse conditions (e.g. blocked pipe or filter, inadequate liquid supply or discharge pressure).

The positioning system stabilizes the diaphragms and virtually eliminates the possibility of incidental diaphragm failure.




# Hydra-Cell® Principles of Operation



## Crank-shaft Models

- 1 Drive Shaft:** via electric motor, hydraulic motor, belt and pulley, etc.
- 2 Precision Ball Bearings:** rigid support, immersed in lubricating oil bath.
- 3 Connecting Rods:** hardened, precision ground, and polished.
- 4 Hydraulic Cells (patented):** displace diaphragms via pressurized oil.
- 5 Diaphragms:** hydraulically balanced, no stress during flexing.
- 6 Inlet Valve Assembly:** simple design, allows liquid into pump chamber.
- 7 Discharge Valve Assembly:** allows liquid to flow into discharge pressure line.
- 8 C46 Pressure Regulating Valve (In-line):** controls output pressure and prevents pump overload.




“Cut-away” view of a Hydra-Cell crank-shaft model shows the patented hydraulic assembly, multiple-diaphragm design, and horizontal disk check valve inlet and discharge assemblies.



# Hydra-Cell® Flow Capacities and Pressure Ratings

## F/M/D/H Series and G Series Seal-less Pumps



The graph above displays the maximum flow capacity at a given pressure for each model series. The table below lists the maximum flow capacity and maximum pressure capability of each model series.

Please Note: Some models do not achieve maximum flow at maximum pressure. Refer to the individual model Performance graphs on subsequent pages for precise flow and pressure capabilities by specific pump configuration.

**Note:** G Series Hydra-Cell Seal-less Pumps are the metric versions of the pumps.

Model <sup>1</sup>	Maximum Capacity gpm (l/min)	Maximum Discharge Pressure psi (bar)		Maximum Operating Temperature F (C) <sup>3</sup>		Maximum Inlet Pressure psi (bar)
		Non-metallic <sup>2</sup>	Metallic	Non-metallic <sup>2</sup>	Metallic	
<b>F20/G20</b>	1.0 (3.8)	350 (24)	1500 (103)	140° (60°)	250° (121°)	250 (17)
<b>M03/G03</b>	3.1 (11.7)	350 (24)	1200 (83)	140° (60°)	250° (121°)	250 (17)
<b>D04/G04</b>	2.9 (11.2)	N/A	2500 (172)	N/A	250° (121°)	500 (34)
<b>D10<sup>4</sup>/G10<sup>4</sup></b>	4.3 (15.1)	N/A	1500 (103)	N/A	250° (121°)	250 (17)
<b>D10/G10</b>	8.8 (33.4)	350 (24)	1000 (69)	140° (60°)	250° (121°)	250 (17)
<b>D12/G12</b>	8.8 (33.4)	N/A	1000 (69)	N/A	250° (121°)	250 (17)
<b>D15 &amp; D17/ G15 &amp; G17</b>	15.5 (58.7)	N/A	2500 (172)	N/A	250° (121°)	500 (34)
<b>H25/G25</b>	20.0 (75.9)	350 (24)	1000 (69)	140° (60°)	250° (121°)	250 (17)
<b>D35<sup>5</sup>/G35<sup>5</sup></b>	23.1 (87.5)	N/A	1500 (103)	N/A	250° (121°)	250 (17)
<b>D35/G35</b>	36.5 (138)	N/A	1200 (83)	N/A	250° (121°)	500 (34)
<b>D66/G66</b>	65.7 (248.7)	250 (17)	700 (48)	120° (49°)	200° (93.3°)	250 (17) <sup>6</sup>

<sup>1</sup> Ratings are for cam design with the highest flow rate.

<sup>2</sup> 350 psi (24 bar) maximum with PVDF liquid end; 250 psi (17 bar) maximum with Polypropylene liquid end.

<sup>3</sup> Consult factory for correct component selection for temperatures from 160°F (71°C) to 250°F (121°C).

<sup>4</sup> D10/G10 @790 rpm maximum.

<sup>5</sup> D35/G35 @700 rpm maximum; consult factory for pressures above 1200 psi (83 bar).

<sup>6</sup> D66/G66 maximum inlet pressure 50 psi (3.4 bar) for non-metallic models.


# F20/G20 Series

Maximum Flow Rate: 1.0 gpm (3.8 l/min)  
 Maximum Pressure: 1500 psi (103 bar) for Metallic Pump Heads  
 350 psi (24 bar) for Non-metallic Pump Heads



F20/G20 close-coupled for 56C frame or IEC 80 footed motors shown. F21/G21 models are shaft driven. F22 models are flexible-coupled to 56C, 143TC and 145TC frame motors; G22 models to IEC 80 - 90 B5 frame motors. Pump head materials include (metallic) Brass, 316L Stainless Steel and Hastelloy C and (non-metallic) Polypropylene and PVDF.

## Maximum Flow at Designated Pressure



S, B & G cam options based on 10 psi (0.7 bar) inlet pressure.

# M03/G03 Series

Maximum Flow Rate: 3.1 gpm (11.7 l/min)  
 Maximum Pressure: 1200 psi (83 bar) for Metallic Pump Heads  
 350 psi (24 bar) for Non-metallic Pump Heads




M03/G13 close-coupled with Polypropylene pump head. Also available in (metallic) Brass, 316L Stainless Steel, Hastelloy CW12MW and (non-metallic) PVDF pump heads.



D03/G03 shaft-driven with 316L Stainless Steel pump head.

## Maximum Flow at Designated Pressure




# M03/G03 Mono-Block Series

Maximum Flow Rate: 3.1 gpm (11.7 l/min)  
 Maximum Pressure: 1000 psi (69 bar) for Metallic Pump Heads



Mono-Block (M03/G13) close-coupled 316L Stainless Steel pump head. Also available in Brass.

## Maximum Flow at Designated Pressure




# D04/G04 Series

Maximum Flow Rate: 2.9 gpm (11.2 l/min)  
 Maximum Pressure: 2500 psi (172 bar) for Metallic Pump Heads



D04/G04 shaft-driven with 316L Stainless Steel pump head. Also available in Brass and 304 Stainless Steel pump heads.

## Maximum Flow at Designated Pressure






# D10/G10 Series

Maximum Flow Rate: 8.8 gpm (33.4 l/min)  
 Maximum Pressure: 1500 psi (103 bar) for Metallic Pump Heads  
 350 psi (24 bar) for Non-metallic Pump Heads




D10/G10 with Cast Iron pump head. Also available in (metallic) Brass, Duplex Alloy 2205 Stainless Steel, 316L Stainless Steel, Hastelloy CW12MW and (non-metallic) Polypropylene and PVDF pump heads.



D10/G10 with 316L Stainless Steel pump head and ANSI flanges.

## Maximum Flow at Designated Pressure




# D12/G12 Series

Maximum Flow Rate: 8.8 gpm (33.4 l/min)  
 Maximum Pressure: 1000 psi (69 bar) for Metallic Pump Heads



D12/G12 equipped with Model C62 Pressure Regulating Valve and Valve/Tube Accessory. Available in Brass, Cast Iron, and 316L Stainless Steel pump heads.

## Maximum Flow at Designated Pressure



## DI5/DI7 & GI5/GI7 Series


Maximum Flow Rate: 15.5 gpm (58.7 l/min)  
 Maximum Pressure: 2500 psi (172 bar) for Metallic Pump Heads



DI5/GI5 for horizontal installations shown with 316L Stainless Steel pump head.


DI7/GI7 for vertical mounting (including motor adapter, base plate and oil reservoir) shown with Brass pump head.

### Maximum Flow at Designated Pressure




## H25/G25 Series

Maximum Flow Rate: 20.0 gpm (75.9 l/min)  
 Maximum Pressure: 1000 psi (69 bar) for Metallic Pump Heads  
 350 psi (24 bar) for Non-metallic Pump Heads



H25/G25 with Cast Iron pump head. Also available in (metallic) Brass, Duplex Alloy 2205 Stainless Steel, 316L Stainless Steel (with ANSI flanges), 316L Stainless Steel, Hastelloy CW12MW and (non-metallic) Polypropylene and PVDF pump heads.

### Maximum Flow at Designated Pressure




## D35/G35 Series

Maximum Flow Rate: 36.5 gpm (138 l/min)  
 Maximum Pressure: 1500 psi (103 bar) for Metallic Pump Heads



D35/G35 with 316L Stainless Steel pump head. Also available in Brass, Ductile Iron, Duplex Alloy 2205 Stainless Steel, 316L Stainless Steel (with ANSI flanges or SAE ports) and Hastelloy CW12MW pump heads.

### Maximum Flow at Designated Pressure




## D66/G66 Series

Maximum Flow Rate: 65.7 gpm (248.7 l/min)  
 Maximum Pressure: 700 psi (48 bar) for Metallic Pump Heads  
 250 psi (17 bar) for Non-metallic Pump Heads



D66/G66 with 316L Stainless Steel pump head. Also available in (metallic) Brass, Ductile Iron, and Duplex Alloy 2205 Stainless Steel, and (non-metallic) Polypropylene pump heads.

### Maximum Flow at Designated Pressure





# C Series Pressure Regulating Valves

Designed for use with any positive displacement pump, Hydra-Cell C Series pressure regulating valves bypass system fluid to prevent excess system pressure. They can also be used as pressure relief valves.

## Performance Advantages

- Accurate and repeatable.
- Adjustable.
- Immediate response.
- Smooth, chatter-free bypass.
- No external springs or moving parts.
- Flow-through design with minimal pressure surge.
- Heavy-duty construction.
- Easy to service in place.



*Tapered design of the C20 Series valves plunger.*



*C60 Series valves feature a seal-less diaphragm with a tapered plunger, making the valves ideal for high-pressure requirements and handling dirty fluids.*

## C20 Series

For use with Hydra-Cell models D10/G10, D12/G12, H25/G25, D35/G35, and D66/G66.

*C22 valve with Brass body (also available in 316L Stainless Steel and Hastelloy CW12MW).*



## C46 Series

For use with Hydra-Cell models F20/G20, F21/G21, F22/G22, M03/D03/G03/G13, and M03/G03 Mono-Block.

*C46 In-line with Brass body.*



*C46 Off-line with Stainless Steel body (also available in Brass).*



## C60 Series

For use with Hydra-Cell models D04/G04, D10/G10, D12/G12, D15/D17 & G15/G17, H25/G25, and D35/G35.

*C62 Seal-less valve with 316L Stainless Steel body (also available in Brass and Hastelloy C).*



# Hydra-Cell® Pumps Accessories and Options



C80 Series Air Bleed Valves.



Pulsation Dampeners.



HDD Series: Horizontal Direct Drive with Orange Coupling Guard, Motor, and Base.



HFD Series: Horizontal Flanged Adapter Drive with Flanged Adapter, Motor, and Base.



HBD Series: Horizontal Belt Drive with Belt Pulley Guard, Motor, and Base.



Controllers.



Control Freak™ Touch-screen Metering Controller. (Also available in a new Web-based version for operation from a phone/mobile device, tablet, or computer.)



Hydra-Oil Lubricants, Motor Adapters, Oil Reservoir Sight Bottles, Tool Kits, and Couplings.



Replacement Parts Kits.




# Hydra-Cell® T & Q Series Design Advantages


**Available  
to Meet  
API 674!**

## Exclusive Seal-less Diaphragm Design

- Seal-less design separates the power end from the process fluid end, eliminating leaks, hazards, and the expense associated with seals and packing.
- Low NPSH requirements allow for operation with a vacuum condition on the suction - positive inlet pressure is not necessary.
- Can operate with a closed or blocked suction line and run dry indefinitely without damage, eliminating downtime and repair costs.
- Unique diaphragm design handles more abrasives with less wear than gear, screw or plunger pumps.
- Hydraulically balanced diaphragms to handle high pressures with low stress.
- Provides low-pulse, linear flow due to its multiple diaphragm design.
- Lower energy costs than centrifugal pumps and other pump technologies.
- Rugged construction for long life with minimal maintenance.
- Compact design provides a variety of installation options – T100 and Q155 models also feature a double-ended shaft for greater versatility.



T100




Q155



# Hydra-Cell® Flow Capacities and Pressure Ratings

## T & Q Series Large Capacity Pumps



Model	Maximum Capacity			Max. Discharge Pressure psi (bar)	Model	Maximum Capacity			Max. Discharge Pressure psi (bar)	Model	Maximum Capacity			Max. Discharge Pressure psi (bar)
	BPD	gpm	l/min			BPD	gpm	l/min			BPD	gpm	l/min	
<b>T100E</b>	3292	96.0	366.1	1500 (103)	<b>Q155E</b>	5383	157	595	1500 (103)	<b>T200K</b>	3189	93	352	3000 (207)
<b>T100F</b>	2623	76.5	289.6	1850 (128)	<b>Q155F</b>	4354	127	490	1850 (128)	<b>T200M</b>	2846	83	314	3500 (241)
<b>T100H</b>	2332	68.0	257.8	2100 (145)	<b>Q155H</b>	3806	111	421	2100 (145)	<b>T200P</b>	2469	72	272	4000 (276)
<b>T100K</b>	1543	45.0	170.4	3000 (207)	<b>Q155K</b>	2674	78	295	3000 (207)	<b>T200Q</b>	2160	63	238	4500 (310)
<b>T100M</b>	1302	38.0	143.8	3500 (241)	<b>Q155M</b>	2160	63	238	3500 (241)					
<b>T100S</b>	891	26.0	98.4	5000 (345)										

# T100 Series Pumps

Available  
to Meet  
API 674!

## Low Pressure Models

### Model T100E

Maximum Flow Rate: 96.0 gpm (366.1 l/min) 3292 BPD  
Maximum Pressure: 1500 psi (103 bar) for Metallic Pump Heads

### Model T100F

Maximum Flow Rate: 76.5 gpm (289.6 l/min) 2623 BPD  
Maximum Pressure: 1850 psi (128 bar) for Metallic Pump Heads

### Model T100H

Maximum Flow Rate: 68.0 gpm (257.8 l/min) 2332 BPD  
Maximum Pressure: 2100 psi (145 bar) for Metallic Pump Heads

*Low-pressure model with Nickel Aluminum Bronze (NAB) pump head.  
Also available in Duplex Alloy 2205 Stainless Steel, 316L Stainless Steel, and Hastelloy CX2M.*



## Medium Pressure Models

### Model T100K

Maximum Flow Rate: 45.0 gpm (170.4 l/min) 1543 BPD  
Maximum Pressure: 3000 psi (207 bar) for Metallic Pump Heads

### Model T100M

Maximum Flow Rate: 38.0 gpm (143.8 l/min) 1302 BPD  
Maximum Pressure: 3500 psi (241 bar) for Metallic Pump Heads

*Medium-pressure model with Nickel Aluminum Bronze (NAB) pump head.  
Also available in Duplex Alloy 2205 Stainless Steel, 316L Stainless Steel, and Hastelloy CX2M.*




## High Pressure Model

### Model T100S

Maximum Flow Rate: 26.0 gpm (98.4 l/min) 891 BPD  
Maximum Pressure: 5000 psi (345 bar) for Metallic Pump Heads

*High-pressure model with Stainless Steel pump head.  
Also available in Nickel Aluminum Bronze (NAB).*



# Q155 Series Pumps

Available  
to Meet  
API 674!

## Low Pressure Models

### Model Q155E

Maximum Flow Rate: 157 gpm (595 l/min) 5383 BPD  
Maximum Pressure: 1500 psi (103 bar) for Metallic Pump Heads

### Model Q155F

Maximum Flow Rate: 127 gpm (490 l/min) 4354 BPD  
Maximum Pressure: 1850 psi (128 bar) for Metallic Pump Heads

### Model Q155H

Maximum Flow Rate: 111 gpm (421 l/min) 3806 BPD  
Maximum Pressure: 2100 psi (145 bar) for Metallic Pump Heads



*Low-pressure model with 316L Stainless Steel pump head.  
Also available in Duplex Alloy 2205 Stainless Steel, 316L Stainless Steel, and Hastelloy CX2M.*

## Medium Pressure Models

### Model Q155K

Maximum Flow Rate: 78 gpm (295 l/min) 2674 BPD  
Maximum Pressure: 3000 psi (207 bar) for Metallic Pump Heads

### Model Q155M

Maximum Flow Rate: 63 gpm (238 l/min) 2160 BPD  
Maximum Pressure: 3500 psi (241 bar) for Metallic Pump Heads



*Medium-pressure model with Nickel Aluminum Bronze (NAB) pump head.  
Also available in Duplex Alloy 2205 Stainless Steel, 316L Stainless Steel, and Hastelloy CX2M.*



# T200 Series Pumps

**Available  
to Meet  
API 674!**

## Medium Pressure Models

### Model T200K

Maximum Flow Rate: 93 gpm (352 l/min) 3189 BPD  
Maximum Pressure: 3000 psi (207 bar) for Metallic Pump Heads

### Model T200M

Maximum Flow Rate: 83 gpm (314 l/min) 2846 BPD  
Maximum Pressure: 3500 psi (241 bar) for Metallic Pump Heads



*Medium-pressure model with Nickel Aluminum Bronze (NAB) pump head.  
Also available in Duplex Alloy 2205 Stainless Steel, 316L Stainless Steel, and Hastelloy CX2M.*

## High Pressure Models

### Model T200P

Maximum Flow Rate: 72 gpm (272 l/min) 2469 BPD  
Maximum Pressure: 4000 psi (276 bar)

### Model T200Q

Maximum Flow Rate: 63 gpm (238 l/min) 2160 BPD  
Maximum Pressure: 4500 psi (310 bar)



*High-pressure model with Nickel Aluminum Bronze (NAB) pump head.  
Also available in Duplex Alloy 2205 Stainless Steel, 316L Stainless Steel, and Hastelloy CX2M.*

# Hydra-Cell® P Series Metering Pumps



**P100**



**P200**



**P300**



**P400**




**P500**



**P600**

## P Series Flow Capacities and Pressure Ratings



*P Series multiple-diaphragm metering pumps exceed API 675 performance standards for Steady-State accuracy ( $\pm 1\%$ ), Linearity ( $\pm 3\%$ ) and Repeatability ( $\pm 3\%$ ) while providing smooth, linear, virtually pulse-free flow.*

Model <sup>1</sup>	Maximum Capacity gph (lph) <sup>2</sup>	Maximum Discharge Pressure psi (bar)		Maximum Operating Temperature F (C) <sup>4</sup>		Maximum Inlet Pressure psi (bar)
		Non-metallic <sup>3</sup>	Metallic	Non-metallic	Metallic	
<b>P100</b>	27.0 (85.0)	350 (24)	1500 (103)	140° (60°)	250° (121°)	250 (17)
<b>P200</b>	81.0 (255.4)	350 (24)	1000 (69)	140° (60°)	250° (121°)	250 (17)
<b>P300</b>	81.4 (256.8)	N/A	2500 (172)	N/A	250° (121°)	500 (34)
<b>P400</b>	242.8 (765.9)	350 (24)	1000 (69)	140° (60°)	250° (121°)	250 (17)
<b>P500</b>	425.9 (1343.5)	N/A	2500 (172)	N/A	250° (121°)	500 (34)
<b>P600</b>	890.3 (2808.0)	350 (24)	1000 (69)	140° (60°)	250° (121°)	250 (17)

<sup>1</sup> Ratings are for X-cam design.

<sup>2</sup> Flow capacities are based on pump speeds of 3600 rpm for gallons per hour (gph) and 3000 rpm for liters per hour (lph).

<sup>3</sup> 350 psi (24 bar) maximum with PVDF liquid end; 250 psi (17 bar) maximum with Polypropylene liquid end.

<sup>4</sup> Consult factory for correct component selection for temperatures from 160°F (71°C) to 250°F (121°C).

# Hydra-Cell® MT8 Low-flow Triplex Metering Pump




This groundbreaking triplex metering pump is the latest addition to the Hydra-Cell Metering Solutions product line. Ideal for low-flow requirements, at high pressures, it features a triplex-diaphragm design to provide smooth, linear, virtually pulse-free flow without the need for expensive pulsation dampeners.

Hydraulically-balanced and actuated, the pump features an integral relief valve for added safety and cartridge check valves for ease of maintenance.


The MT8 is available with metallic (316 SST, Hastelloy C, Alloy 20) and non-metallic (PVC, PVDF) liquid ends plus PTFE diaphragms. Check valve materials include 316 SST, Hastelloy C, and Alloy 20.

## Exceeds API 675 Performance Standards


Hydra-Cell Metering Solutions model MT8 pumps exceed API 675 performance standards for Steady-State Accuracy ( $\pm 1\%$ ), Linearity ( $\pm 3\%$ ), and Repeatability ( $\pm 3\%$ ).




With its multiple-diaphragm design, the MT8 provides virtually pulse-free flow.



Duplexing capability doubles capacity and savings.



MT8 with PVDF pump head.



ATEX-compliant manual variable speed gearbox.

## Flow Capacities and Pressure Ratings

Model	Minimum to Maximum Capacity gph (lph)	Maximum Discharge Pressure psi (bar)		Maximum Operating Temperature F (C) <sup>2</sup>		Maximum Inlet Pressure psi (bar)
		Non-metallic <sup>1</sup>	Metallic	Non-metallic	Metallic	
<b>MT8</b>	0.06 to 8.00 (0.227 to 30.28)	350 (24)	3500 (241)	140° (60°)	250° (121°)	250 (17)

<sup>1</sup> 350 psi (24 bar) maximum with PVDF liquid end; 250 psi (17 bar) maximum with PVC liquid end.

<sup>2</sup> Consult factory for correct component selection for temperatures from 160°F (71°C) to 250°F (121°C).



# Hydra-Cell® S Series Solenoid Metering Pumps

The S Series diaphragm pumps provide an economical choice for chemical injection in metering applications.

Solenoid driven, the S pumps feature a wide discharge-volume range, extensive choice of liquid end materials, various control functions, and a wide voltage range.

Materials of construction choices and versatile design options result in pumps perfected for specific applications including general chemicals, high-pressure boiler, high-viscosity fluids, outgassing and more.



SM030CAS manual control with stroke speed dial. Model shown features Acrylic pump head with automatic air release joint for outgassing fluids.



SP060HVS digital with pulse-input control. Model shown features PVC pump head for high-viscosity fluids.



ST03RPES digital with pulse-input control and timer. ST models offer control options by interval, day, and week.



SA03RPES digital with pulse-input and analog-input. Model shown features an integral relief valve to release abnormal pressure automatically.

## SM Models Flow Capacities and Pressure Ratings

Model Number	Maximum Discharge Volume			Maximum Discharge Pressure	
	ml/min	gph	lph	psi	bar
SM030 High Pressure	28	0.44	1.68	217	15
SM030	30	0.48	1.80	145	10
SM060	60	0.95	3.60	116	8
SM100	100	1.59	6.00	58	4
SM03R* High Pressure	28	0.44	1.68	217	15
SM03R*	30	0.48	1.80	102	7
SM06R*	60	0.95	3.60	102	7
SM10R*	100	1.59	6.00	58	4

\*Models equipped with internal relief valve.

### Stroke Speed:

15 to 300 strokes/minute  
(manual dial setting)

### Stroke Length:

Fixed at 1.0 mm

### Temperature Range:

32°F to 104°F (0°C to 40°C)

### Ambient Humidity:

35% to 85%

## SP/ST/SA Models Flow Capacities and Pressure Ratings

Model Number	Maximum Discharge Volume			Maximum Discharge Pressure	
	ml/min	gph	lph	psi	bar
SP, ST or SA030 High Pressure	25	0.40	1.50	290	20
SP, ST or SA030	30	0.48	1.80	145	10
SP, ST or SA060	60	0.95	3.60	145	10
SP, ST or SA100	100	1.59	6.00	58	4
SP, ST or SA200	220	3.49	13.20	29	2
SP, ST or SA03R* High Pressure	28	0.44	1.68	217	15
SP, ST or SA03R*	30	0.48	1.80	145	10
SP, ST or SA06R*	60	0.95	3.60	102	7
SP, ST or SA10R*	100	1.59	6.00	102	7

\*Models equipped with internal relief valve.

### Stroke Speed:

1 to 300 strokes/minute  
(enables setting in 1-stroke units)

### Stroke Length:

0.5 mm to 1.0 mm (enables adjustment using the dial)

### Temperature Range:

32°F to 104°F (0°C to 40°C)

### Ambient Humidity:

35% to 85%

# Additional Wanner Engineering Pumps

## Non-metallic ANSI Centrifugal Pumps

# STAN-COR

- Solid PVDF pump head for chemical compatibility and excellent abrasion resistance.
- Operates with a smooth, full-curve performance.
- Concentric casing design for better flow patterns than other centrifugal pumps - less turbulence, longer seal life, and reduced shaft deflection.
- Handles high operating temperatures.
- Compact design features including heavy-duty drive shaft, adjustable bearing supports, and large-capacity oil bath ensure low maintenance as well as durable performance for the toughest fluid applications.
- Back pull-out design for easy servicing.
- Handles solid sizes up to 9/16" maximum.




*Designed to handle difficult process fluids, Stan-Cor pumps offer total dynamic head to 350 feet and flow rate capacities to 700 gpm (2650 l/min).*

## Peristaltic Pumps that Isolate the Pumped Fluid

# VECTOR

- Dry pump cavity.
- Self-priming operation.
- Runs dry without damage to the pump.
- Complete isolation of the fluid being pumped from contact with mechanical parts for the fluid transport system.
- Heavy-duty roller bearings.
- Wide range of pump configurations and flow rates.
- No cups, packing, or dynamic seals to leak or replace or come in direct contact with the pumped fluid.
- Low maintenance.
- Reversible flow.



*Nine 2000 Series Vector pump models (2006 shown) offer maximum flow rates from 0.3 gpm (1.1 l/min) to 211 gpm (798.7 l/min) and discharge pressures from 30 psig (2.1 bar) to 116 psig (8 bar) depending on pump model. Model 3005 provides up to 9.2 gpm (34.8 l/min) at 200 psig (13.8 bar).*

*Seven 4000 Series Vector pump models offer maximum flow rates from 0.79 gpm to 154.1 gpm and discharge pressures of 110 psig or 218 psig depending on pump model.*

# Hydra-Cell® Worldwide Sales and Service



Hydra-Cell pumps are sold and serviced worldwide by a comprehensive network of factory-trained pump distributors. As specialists in pump technologies, our distributor organizations offer you a vital local resource for technical expertise, product training, sales and service.

Hydra-Cell distributors are located in more than 70 countries worldwide. In North America specifically, there are more than 100 Hydra-Cell distributor locations to provide local availability for every major commercial, institutional, industrial, and municipal marketplace.

## World Headquarters & Manufacturing

★ Minneapolis, Minnesota, USA

## Business Units

- ☀ Wichita Falls, Texas, USA
- ☀ Hampshire, United Kingdom
- ☀ Kowloon, Hong Kong
- ☀ Shanghai, China
- ☀ São Paulo, Brazil

## Contact us for the name and location of the authorized Hydra-Cell distributor nearest you:

Algeria	Colombia	India	Mongolia	Russia	Thailand
Argentina	Costa Rica	Indonesia	Morocco	Saudi Arabia	Tunisia
Australia	Czech Republic	Ireland	Netherlands	Serbia	Turkey
Austria	Denmark	Israel	New Zealand	Singapore	Ukraine
Azerbaijan	Ecuador	Italy	Norway	Slovakia	United Arab Emirates
Belarus	Egypt	Japan	Oman	Slovenia	United Kingdom
Belgium	Estonia	Kazakhstan	Panama	South Africa	United States
Bolivia	Finland	Kuwait	Peru	South East Asia	Uruguay
Brazil	France	Latvia	Poland	South Korea	Venezuela
Bulgaria	Germany	Lithuania	Portugal	Spain	Viet Nam
Canada	Greece	Luxembourg	Puerto Rico	Sweden	Yemen
Chile	Hong Kong	Malaysia	Qatar	Switzerland	
China	Hungary	Mexico	Romania	Taiwan	



# Hydra-Cell®

## Seal-less Pumps

### Wanner Engineering, Inc.

#### World Headquarters & Manufacturing

Wanner Engineering, Inc.  
1204 Chestnut Avenue  
Minneapolis, MN 55403 USA  
Phone: 612-332-5681 • Fax: 612-332-6937  
Toll-Free Fax (USA): 800-332-6812  
Email: sales@wannereng.com  
www.Hydra-Cell.com

#### Regional Office

207 US Highway 281  
Wichita Falls, TX 76310 USA  
Phone: 940-322-7111  
Toll-Free: 800-234-1384  
Email: sales@wannereng.com  
www.Hydra-Cell.com

#### Latin American Office

Avenida Senador Vergueiro 608 - Centro  
São Bernardo do Campo/São Paulo, Brazil  
CEP 09750-000  
Phone: +55 (11) 99582-1969  
Email: mmagoni@wannereng.com  
www.Hydra-Cell-Pumps.com.br

### Wanner International Ltd.

Wanner International, Ltd.  
Hampshire - United Kingdom  
Phone: +44 (0) 1252 816847  
Email: sales@wannerint.com  
www.Hydra-Cell.co.uk

### Wanner Pumps Ltd.

Wanner Pumps, Ltd.  
Kowloon - Hong Kong  
Phone: +852 3428 6534  
Email: sales@wannerpumps.com  
www.WannerPumps.com

Shanghai - China  
Phone: +86-21-6876 3700  
Email: sales@wannerpumps.com  
www.WannerPumps.com

